

TECHNICAL SPECIFICATION

STERLING ROYALE

Roll Dimension

Length (m)	Width	Area (m ²)
7.3	1.37	10

Thickness	Weight	BS 5808	BS 4790
mm +/- 10%	g/m ² +/- 10%	Classification	Flammability
11.5mm	2445	L/U	Pass - Low Radius

BS 4745
Thermal Insulation
2.48 Tog

Acoustic Performance, Practical Absorption Coefficient

250	500	1000	2000	4000
0.25	0.65	1	0.9	0.8

Comfort / Durability	Recommendations	Living	Hall Stairs Landing	Heavy Floor Wheel Traffic Castor Chairs
10/10	* Bedrooms	*	*	*

Installation

Subfloors should be dry, clean and free of oil, grease & damp.

Fitting should meet the British Standard code of practice BS 5325 & be undertaken by experienced fitters

- ✓ Suitable
- * Highly Recommended



www.envirolay.co.uk

Please note: This document does not constitute a manufacturing specification. It details important technical performance and physical characteristics of the product only. Please contact the Technical Department for any further information.

Telephone **+44 (0) 1274 905411**

Facsimilie **+44 (0) 1274 905412**

Email **sales@textfelt.co.uk**

Website **www.textfelt.co.uk**